

Breathing Protection

TD-16518-00

Product data sheet uvex silv-Air 5100 FFP1 NR D



Product information

1 Toddet information			
Product	Particle-filtering folding mask without valve		
features	Protection level FFP1		
	 Innovative design with optimized shape 		
	Soft material edges for high wearing comfort		
	Continuous head band (adjustable) for a comfortable and		
	secure fit		
	The masks are individually packed		
	Flexible and adjustable nose clip		
	Compatible with uvex safety eyewear		
	Soft sealing lip (nose area) guarantees a secure,		
	comfortable sealed position of the mask		
	Mask fulfils the requirements of the dolomite dust test (D)		
Materials	Headband: textile		
	Adjustment piece: silicone		
	Nose clip: PP		
	Filter/mask: Melt blown PP, Polyester		
	Sealing lip: EVA foam		
Weight	12 g		
Standard	EN 149:2001 + A1:2009		

Versions

Article number	Colour/Version	Retail unit
8765.100	folding mask FFP1, white without valve	30 pcs. per box

Date: 08.02.2018 Page 1 of 2

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to **4 times** the respective limit values.

Particles (neither toxic nor associated with fibrosis), Agriculture, hay, food industry, grain, flour, graphite, chalk, marble, rust.

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Date: 08.02.2018 Page 2 of 2