

Product data sheet flat fold mask FFP2 NR D, EN 149:2001 – uvex silv-Air 8203



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product features	<ul style="list-style-type: none">• Particle-filtering flat fold mask without valve• Protection level FFP 2• Soft material edges for increased comfort• Seamless, continuous headband for a comfortable, secure fit• Integrated, flexible, adjustable nose clip• Hydrophobic coating• Foam pads at chin and nose area offers a perfect fit• The masks are individually packed• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: synthetic latex Nose clip: metal, PP Sealing lip: synthetic foam Filter / mask: PP, Polyester

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Mining, chemical industry, shipyards, iron and steel industry, woodworking, dust and fumes of substances such as asbestos, quartz, aluminum, copper, barium, titanium, vanadium, chrome, manganese and coal dust with more than 10% free silicon dioxide.
Weight	9 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8708.203	Flat fold mask FFP2, silver without valve	20 pieces per box