

Product data sheet flat fold mask FFP2 NR D, EN 149:2001 – uvex silv-Air 8213



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product features

- Particle-filtering flat fold mask with exhalation valve
- Protection level FFP 2
- Soft material edges for increased comfort
- Seamless, continuous headband for a comfortable, secure fit
- Integrated, flexible, adjustable nose clip
- Hydrophobic coating
- Foam pads at chin and nose area offers a perfect fit
- Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask
- The masks are individually packed
- Mask fulfils the requirements of the dolomite dust test (D)

Materials

Headband: synthetic latex
Nose clip: metal, PP
Sealing lip: synthetic foam
Filter / mask: PP, Polyester
Valve: PP

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Mining, chemical industry, shipyards, iron and steel industry, woodworking, dust and fumes of substances such as asbestos, quartz, aluminum, copper, barium, titanium, vanadium, chrome, manganese and coal dust with more than 10% free silicon dioxide.
Weight	15 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8708.213	Flat fold mask FFP2, silver with valve	15 pieces per box