

Product data sheet flat fold mask FFP3 NR D, EN 149:2001 - uvex silv-Air 3310



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<b>Product features</b>	<ul style="list-style-type: none"><li>• Particle-filtering flat fold mask with exhalation valve</li><li>• Protection level FFP 3</li><li>• Soft material edges for high wearing comfort</li><li>• The adjustable head band offers an easy handling and comfortable fit</li><li>• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li><li>• Flexible and adjustable nose clip</li><li>• The masks are individually packed</li><li>• Soft sealing lip guarantees a secure, comfortable sealed position of the mask</li><li>• Compatible with uvex safety eyewear</li><li>• Mask fulfils the requirements of the dolomite dust test (D)</li></ul>
<b>Materials</b>	Headband: textile Nose clip: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS

<b>Areas of use</b> The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to <b>30 times</b> the respective limit values.	Welding, soldering, high concentrations of very hazardous and microscopic respirable dust and with chemical compounds that contain beryllium, stibium, arsenic, cadmium, cobalt, nickel, platinum, radium or strychnine.
<b>Weight</b>	15 g
<b>Standard</b>	EN 149:2001 + A1:2009

### Versions

Article number	Colour/Version	Retail unit
8733.310	Flat fold mask FFP3, white with valve	15 pieces per box
8753.310	Flat fold mask FFP3, white with valve	3 pieces in retail packaging
8753.311	Flat fold mask FFP3, white with valve	2 pieces in retail packaging