

Product data sheet cup shape mask FFP2 NR D with Carbon, EN 149:2001 – uvex silv-Air 2220



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product features

- Particle-filtering cup shape mask with exhalation valve
- Protection level FFP2
- Soft material edges for high wearing comfort
- Continuous head band for a comfortable and secure fit
- Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask
- Flexible and adjustable nose clip
- Compatible with uvex safety eyewear
- Soft sealing lip guarantees a secure, comfortable sealed position of the mask
- Activated carbon filter for odors, gases and vapors below limit value
- Mask fulfils the requirements of the dolomite dust test (D)

Materials

Headband: textile
Nose clip: aluminum
Filter / mask: Melt Blown PP, Polyester
Sealing lip: PVC foam
Valve: ABS

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Mining, chemical industry, shipyards, iron and steel industry, woodworking, dust and fumes of substances such as asbestos, quartz, aluminum, copper, barium, titanium, vanadium, chrome, manganese and coal dust with more than 10% free silicon dioxide.
Weight	20 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8732.220	cup shape mask FFP2, white with valve and carbon	15 pieces per box