

Product data sheet flat fold mask FFP3 NR D, EN 149:2001 – uvex silv-Air 8313



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product features

- Particle-filtering flat fold mask with exhalation valve
- Protection level FFP 3
- Soft material edges for increased comfort
- 4-point headband attachment allows an individual and secure fit
- Integrated, flexible, adjustable nose clip
- Hydrophobic coating
- Soft sealing lip guarantees a secure, comfortable sealed position of the mask
- Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask
- The masks are individually packed
- Mask fulfils the requirements of the dolomite dust test (D)

Materials

Headband: textile
Nose clip: metal, PP
Sealing lip: Synthetic foam
Filter / mask: PP, Polyester
Valve: PP

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Welding, soldering, high concentrations of very hazardous and microscopic respirable dust and with chemical compounds that contain beryllium, stibium, arsenic, cadmium, cobalt, nickel, platinum, radium or strychnine.
Weight	23 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8708.313	Flat fold mask FFP3, silver with valve	15 pieces per box