

### Product data sheet uvex silv-Air 5200+ FFP2 NR D



#### Product information

<b>Product features</b>	<ul style="list-style-type: none"><li>• Particle-filtering folding mask with exhalation valve</li><li>• Protection level FFP2</li><li>• Ergonomically adapted for larger face shapes</li><li>• Innovative design with optimized shape</li><li>• Soft material edges for high wearing comfort</li><li>• Continuous head band (adjustable) for a comfortable and secure fit</li><li>• The masks are individually packed</li><li>• Flexible and adjustable nose clip</li><li>• Compatible with uvex safety eyewear</li><li>• Soft sealing lip (nose area) guarantees a secure, comfortable sealed position of the mask</li><li>• Mask fulfils the requirements of the dolomite dust test (D)</li></ul>
<b>Materials</b>	Headband: textile Adjustment piece: silicone Nose clip: PP Filter/mask: Melt blown PP, Polyester Sealing lip: EVA foam
<b>Weight</b>	12 g
<b>Standard</b>	EN 149:2001 + A1:2009

#### Versions

Article number	Colour/Version	Retail unit
8765.201	Folding mask FFP2, white without valve, large version	30 pcs. per box
8765.200	Folding mask FFP2, white without valve, small to medium version	30 pcs. per box

### Areas of use\*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to <b>10 times</b> the respective limit values.	Woodworking, softwood, cement, metal, smog, fine dust, concrete, iron dust, ash, cotton dust, fluoride, carbon fibres, gypsum, fibre glass, copper, nickel, soot, pollen, house dust, pet hair.
--	---

\*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advice.